

Panasonic recommends Windows.

Panasonic



TOUGHPAD FZ-E1

- Windows® Operating System
- Voice and Data Technology
- Qualcomm® Quad-core Processor
- MIL-STD-810G, 10' Drop, All-weather IP65 and IP68 Dust and Water-resistant Design
- 14-hour Hot-swappable Battery
- Optional Integrated Barcode Reader, Magstripe Reader and Certified ANSI 12.12.01 for Hazardous Locations
- Glove-enabled Multi Touch Daylight-readable Display
- 3-year Warranty with Business Class Support

10-FOOT
DROP RATING

IP65

IP68

MIL-STD-
810G

THE WORLD'S MOST RUGGED 5" HANDHELD TABLET, WITH VOICE AND DATA TECHNOLOGY.

The new Panasonic Toughpad® FZ-E1 is the world's most rugged 5" handheld tablet, with optional data and voice technology. This fully-rugged tablet is MIL-STD-810G and IP65/68 tested with a 10' drop resistance, operating temperature of -4°F to 140°F and a glove-enabled multi touch daylight-readable display. The Toughpad FZ-E1 boasts the world's longest battery life for a handheld tablet, with 14 hours of continuous data access. The battery quickly charges to 50% in just one hour, and is hot-swappable. Customized options include integrated barcode reader, magstripe reader and certified ANSI 12.12.01 for hazardous locations.

For more information Contact TransCOR:
1-888-RUGGED-3
TransCOR-IT.com
Rugged@TransCOR-IT.com



TOUGHPAD®

TOUGH PAD FZ-E1



Panasonic

Panasonic recommends Windows.

DURABILITY	<ul style="list-style-type: none">World's most rugged designMIL-STD-810G (shock, vibration, rain, dust, sand, altitude, freeze/thaw, high/low temperature, temperature shock, humidity, explosive atmosphere)IP65 and IP68 sealed all-weather design (submersible up to 5' for 30 minutes)10' drop-resistantOperating temperature of -4°F to 140°FPort coversRaised bezel for LCD impact protection						
SOFTWARE	<ul style="list-style-type: none">Windows® Embedded 8.1 Handheld						
CPU	<ul style="list-style-type: none">Qualcomm® MSM8974AB 2.3GHz Quad-core						
STORAGE & MEMORY	<ul style="list-style-type: none">Memory 2GB^{1,2}Storage 32GB^{1,2}<ul style="list-style-type: none">Up to 64GB additional with optional microSDXC card³						
DISPLAY	<ul style="list-style-type: none">5" high definition 1280 x 720 daylight-viewable display10-point capacitive gloved multi touch with glove touch mode<ul style="list-style-type: none">Rain sensing touch mode2-500 nitVA display with direct bondingAnti-reflective and anti-glare screen treatmentsAutomatic screen rotation						
AUDIO	<ul style="list-style-type: none">Integrated microphone x 3Loud volume twin speakers 100 db						
KEYBOARD & INPUT	<ul style="list-style-type: none">10-point gloved multi touch + digitizer screen2-4 tablet buttons (user-definable)On-screen QWERTY keyboard						
SENSORS	<ul style="list-style-type: none">Ambient light sensor, digital compass, gyro and acceleration sensors						
CAMERAS	<ul style="list-style-type: none">HD 1.3MP webcam8MP rear camera with LED light						
EXPANSION	<ul style="list-style-type: none">microSDXC						
INTERFACE	<table><tr><td>Docking connector</td><td>13-pin</td></tr><tr><td>USB 2.0 (x 1)⁴</td><td>4-pin</td></tr><tr><td>Headphone & microphone</td><td>Mini-jack stereo</td></tr></table>	Docking connector	13-pin	USB 2.0 (x 1) ⁴	4-pin	Headphone & microphone	Mini-jack stereo
Docking connector	13-pin						
USB 2.0 (x 1) ⁴	4-pin						
Headphone & microphone	Mini-jack stereo						
WIRELESS	<ul style="list-style-type: none">IEEE802.11 a/b/g/n/ac4G LTE, HSPA+, UMTS, EDGE, GPRS, CDMA 1x, EVDO Rev.AMicro SIM card slot x 2Bluetooth® v4.0 (class 1)GPS 2m CEP50 (±2 to 4m)Near Field Communication (NFC)<ul style="list-style-type: none">Felica Type A, Type B						
POWER SUPPLY⁵	<ul style="list-style-type: none">Li-Ion battery pack 3.8V, 6200mAhBattery operation:<ul style="list-style-type: none">Standby up to 1000 hours; Talk up to 23 hours; Barcode up to 20.5 hoursBridge battery:<ul style="list-style-type: none">30 seconds to 2 minutesContinuous use data:<ul style="list-style-type: none">14 hoursBattery charging time:<ul style="list-style-type: none">Power on approx. 3.6 hours; 50% charge in approx. 1 hourAC adapter sold separately						
POWER MANAGEMENT	<ul style="list-style-type: none">Consumption approx. 18WHot-swappable battery						
SECURITY FEATURES	<ul style="list-style-type: none">FIPS140-2 level-1 compliantARM® TrustZone® (Built-in)						
WARRANTY	<ul style="list-style-type: none">3-year limited warranty, parts and labor						
DIMENSIONS & WEIGHT⁶	<ul style="list-style-type: none">6.5"(L) x 3.4"(W) x 1.2"(H)Approx. 0.94 lb.						

INTEGRATED OPTIONS⁷

- Optional 1D/2D barcode reader
- Optional magnetic stripe reader with hand strap and stylus
- Certified ANSI 12.12.01 for hazardous locations

ACCESSORIES⁸

AC Adapter (60W) for Device and Desktop Cradle ⁸ (sold separately from device, included with cradle)	CF-AA6373AM
AC Adapter (110W) for 4-Bay Cradle and 4-Bay Battery Charger (included with both cradles)	CF-AA5713AM
Car/DC Adapter	CF-AAV1601AW
Desktop Cradle with Spare Battery Charging Slot (60W power adapter included)	TBD
4-Bay Cradle (110W power adapter included)	FZ-VEBX121M
4-Bay Battery Charger (110W power adapter included)	FZ-VCBX111M
Hand Strap with Stylus (corner rings included)	TBD
Holster and Belt	FZ-VSTX111U
Battery Pack	FZ-VZSUX100J
Shoulder Strap (corner rings included)	TBD
Vehicle Dock	TBD

Please consult your reseller or Panasonic representative before purchasing.

¹ 1GB = 1,000,000,000 bytes.

² Total usable memory will be less depending upon actual system configuration.

³ Operation has been tested and confirmed using Panasonic SD Memory Card with a capacity of up to 2GB, Panasonic SDHC Memory Card with a capacity of up to 32GB, and Panasonic SDXC Memory Card with a capacity of up to 64GB. Operation on other SD equipment is not guaranteed.

⁴ Does not guarantee operation of all USB-compatible peripherals.

⁵ Approximate time. Battery performance features such as charge time and life span can vary according to the conditions under which the computer and battery are used. Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other customer preferences. 14 hours based on Panasonic test conditions. Talk time may change according to cellular network condition. Measured with VOIP application.

⁶ Length measurements do not include protrusions. Weight varies with options.

⁷ Accessories and Integrated Options may vary depending on your configuration. Visit Panasonic website for more accessories and details.

⁸ The AC adapter is compatible with power sources up to 240V AC adapter. The AC adapter is sold separately.



LASER RADIATION
DO NOT STARE INTO BEAM
CLASS 2 LASER PRODUCT
3mW MAX. 635-690 nm
EN 60825-1:2007 IEC60825-1:2007

For more information Contact TransCOR:
1-888-RUGGED-3
TransCOR-IT.com
Rugged@TransCOR-IT.com



TOUGH PAD